


General purpose 25 amp Power Relay available in two and three pole versions, Flange mounted

- Arc barriers prevent flashover between contacts
- Manual operator for circuit testing option
- LED operator for circuit testing option
- High reliability/long life expectancy
- UL, CSA



## Options and ordering codes




## Specifications

	2 pole	3 pole
<b>Rated load resistive</b>	25A@277VAC/20A@28VDC	20A@277VAC/15@28VDC
<b>Motor load</b>	1.5HP 240VAC	1HP 240VAC
<b>Operate time</b>	25ms maximum	
<b>Release time</b>	20ms maximum	
<b>Maximum operate frequency</b>	1200 ops/hr at maximum rated load, 18000 ops/hr mechanical	
<b>Dielectric strength</b>	1600VAC 50/60Hz for 1 minute	
<b>Ambient operating temperature</b>	-45° ~ +70°C	
<b>Mechanical service life</b>	10 million ops. minimum	
<b>Electrical service life</b>	100,000 ops at rated load	
<b>Weight</b>	79.2g	
<b>Power consumption</b>	2.0VA AC 1.2 watts DC	

## Coil Data

Rated Voltage	AC Coils		DC Coils	
	Coil Resistance (Ω)	Rated Current (mA)	Coil Resistance (Ω)	Rated Current (mA)
12	18	283	120	100
24	72	142	472	51
110	1580	31	10000	11
230	7200	15	-	-

## Dimensions (mm)



## Terminal arrangement

